

ROBUS®

OUTDOOR

GUIDELUX LED DUAL WATTAGE BOLLARD

10/15W, IP65



RGD15XCF-25



RGD15XSF-25



RGD15XLD-25

PRODUCT INFORMATION DOCUMENT

CONSTRUCTION

- Die cast aluminium housing
- Polycarbonate diffuser
- Prewired with 1.1m rubber flex

FEATURES

- The GUIDELUX bollard range features a modular construction, allowing users to choose from three bollard head designs mounted on either a 600mm or 800mm pole, with a concrete anchor kit sold separately
- The anchor kit and expansion bolts are crafted from durable stainless steel 316 for enhanced corrosion resistance
- Allows selection between 10W and 15W power output and 3000K and 4000K colour temperature
- Each of the heads equipped with photocell allowing automatic switching on/off at dusk and dawn
- IP67 rated loop-in loop-out junction box in the base of the bollard, which is fitted to work with armoured cables
- High quality powder coating enhancing weather protection and aesthetics



WARRANTY



LIFETIME



LUMENS PER W



IK RATING



IP RATING



OPERATING VOLTAGE



BEAMANGLE



DIMMING



CCT



SAFETY CLASS

Product Code:	RGD15XCF-25	RGD15XSF-25	RGD15XLD-25
Comparable to:	50W/70W halogen	30W/50W halogen	30W/50W halogen
Total Power (W):	10.2/15.2	10.1/14.9	9.9/14.7
Power Factor:	0.9	0.9	0.9
Total Light Output (lm):	780/1120	480/700	510/740
Total Emergency Light Output (lm):	NA	NA	NA
Efficacy (lm/cctW):	76/75	48/47	51/50
Lux at 1m (lux):	40/60	40/60	20/30
Emergency Lux at 1m (lux):	NA	NA	NA
CCT (K):	3000/4000	3000/4000	3000/4000
CRI:	80	80	80
SDCM:	6	6	6
UGR:	28.6	30.4	28.0
IP:	65	65	65
Operation Temperature (°C):	-20 ≤ Ta ≤ +45	-20 ≤ Ta ≤ +45	-20 ≤ Ta ≤ +45
Energy Class:	C	C	C
Rated Life to L70B50 (Hrs):	192000	192000	192000
Rated Life to L80B10 (Hrs):	54000	54000	54000
Rated Life to L90B10 (Hrs):	54000	54000	54000
Dimensions ØxH (mm):	120x212	120x163	120x249
Weight (kg):	1.3	1.1	1.35

Separate Control Gear Information			
Type of Light Source:	LED	LED	LED
Full Load Efficiency (%):	87	87	87
P _{NET} (W):	NA	NA	NA
Dimensions (mm):	76x45x26	76x45x26	76x45x26

Product is certified to all the relevant standards.

Please contact our technical department for market specific compliances.

PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000
 UK: TEL: 0800 973 220
 AUS: TEL: +61 7 3890 5444
 NZ: TEL: +64 03 668 5285

WEB: ROBUS.COM
 WEB: ROBUS.COM
 WEB: ROBUS.COM.AU
 WEB: ROBUSLED.CO.NZ

LED GROUP EUROPE · UK · AUSTRALIA · NEW ZEALAND · ASIA · MIDDLE EAST · AFRICA

GUIDELUX LED DUAL WATTAGE BOLLARD

10/15W, IP65

Cone Illuminance Diagram




Diagram for RGD15XCF-25 in 15W 4000K. Other diagrams available on request

Polar Intensity Diagram






Diagram for RGD15XCF-25 in 15W 4000K. Other diagrams available on request

Dimension Diagram



Item	H	H1	H2	D	Weight
RGD15XSF-25	163mm	111.4mm	32mm	Ø120mm	1.10kg
RGD15XCF-25	212mm	161.4mm	32mm	Ø120mm	1.30kg
RGD15XLD-25	249mm	198.7mm	32mm	Ø120mm	1.35kg



Accessories

- RGD6P-25 600mm Pole c/w IP68 Junction Box
- RGD8P-25 800mm Pole c/w IP68 Junction Box
- RGDAK Concrete Anchor Kit

PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000
 UK: TEL: 0800 973 220
 AUS: TEL: +61 7 3890 5444
 NZ: TEL: +64 03 668 5285

WEB: ROB.US.COM
 WEB: ROB.US.COM
 WEB: ROB.US.COM.AU
 WEB: ROB.USLED.CO.NZ

LED GROUP EUROPE · UK · AUSTRALIA · NEW ZEALAND · ASIA · MIDDLE EAST · AFRICA